



PROPOSAL



Villager 4 Gas

FEATURES & BENEFITS

- FE 350 gas engine provides better acceleration allowing your customers to take on hills all other challenges.
- AlumiCore™ chassis eliminates rusting and corrosion, extending the Villager 4's lifespan significantly
- Carries up to 4 passengers
- SportDrive™ steering and suspension provide an invigorating, sports car-like driving experience
- Impact and UV resistant body panels with 360 degree bumper system
- Ergonomic seats with contoured seat bottom ensures the most comfortable ride anywhere
- Fuel gauge/hour meter standard
- Dual dash compartments and quad cup holders
- Wheel covers standard
- Maximum speed of 15 mph (24 kph)
- Industry's best limited warranty

POWER SOURCE	
Engine	Kawasaki® 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter
Horsepower	10.4 hp (7.65 kW) rated @3600 rpm per SAE J1349
Governor	Automatic ground speed sensing
Drive Unit	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
Battery	12-volt 500 CCA 105 min Reserve
STEERING / SUSPENSION	
Steering	SportDrive™ with self-adjusting rack and pinion
Suspension	Independent leaf spring with dual hydraulic shocks
Brakes	Rear-wheel, mechanical drum
Park Brake	Foot-operated, multi-lock
BODY / CHASSIS	
Frame Chassis	Aluminum box beam with composite cross member
Body	Formion®, Molded-in color
Tires	18 x 8.50-8, 4-ply rated, premium tread
Instrumentation	Electronic fuel gauge/hour meter, low-oil warning light
DIMENSIONS	
Total Vehicle Capacity	800 lb (362.9 kg)
Seating Capacity	4
Overall L x W x H	104.0 x 47.3 x 68.5 in (264.2 x 120.1 x 174.0 cm)
Wheelbase	65.5 in (166.4 cm)
Ground Clearance	4.5 in (11.4 cm)
Fuel Tank Capacity	6.7 gal (25.4 L)
Tread (Front/Rear)	34.5 in/38.6 in (87.6 cm/97.8 cm)
Dry Weight	735 lb (333 kg)
Outside Radius Circle	17.3 ft (5.3 m)
Turning Radius	8.4 ft (2.6 m)
Intersecting Aisle Radius	6 ft (1.8 m)
Speed Range	12-15 mph (19-24 km/h)
Vehicle Warranty	3 yr/3000 hr limited powertrain/frame; 2 yr limited remaining vehicle