



PROPOSAL



Villager 8 Gas

FEATURES & BENEFITS

- Powerful 14.0 hp (10.3 kW) Subaru® engine with Electronic Fuel Injection (EFI)
- Rustproof aircraft grade aluminum frame
- Independent front suspension with self-adjusting rack and pinion steering
- Carries up to 8 passengers
- Fixed Rear Seat Standard, Fold Down Rear Seat Available
- Taillights, Brake Lights, Halogen Headlights, and Horn
- Dual dash compartments
- Maximum speed of 17 mph (27 kph)
- ArmorFlex® front body for fade-resistant color
- Industry's Best 2-year limited warranty

POWER SOURCE	
Engine	Subaru, EFI 4-cycle, OHC, 404 cc, single-cylinder, air-cooled, splash-lubricated
Horsepower	14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940
Governor	Automatic ground speed sensing
Drive Unit	Unitized transaxle, helical gears: 11.47:1 forward; 15.63:1 reverse
Battery	12-volt 500 CCA 105 min Reserve
STEERING / SUSPENSION	
Steering	Self-adjusting rack & pinion
Suspension	Independent leaf spring with dual hydraulic shocks
Brakes	4-wheel, mechanical drum
Park Brake	Foot-operated, multi-lock
Stabilizer Bar	Yes
BODY / CHASSIS	
Frame Chassis	Aluminum I-beam
Front Body	ArmorFlex® with automotive paint/clearcoat
Body Color	Matching paint over molded in color
Tires	18 x 6.50-8, 6-ply rated, premium tread
Light Package	Standard
Instrumentation	Electronic fuel gauge/hour meter, low-oil warning light
DIMENSIONS	
Total Vehicle Capacity	1500 lb (681 kg)
Seating Capacity	8
Overall L x W x H	157.0 x 47.3 x 48.0 in (398.8 x 120.1 x 121.9 cm)
Wheelbase	131.5 in (334 cm)
Ground Clearance	4.5 in (11.4 cm)
Fuel Tank Capacity	4.6 gal (17.4L)
Tread (Front/Rear)	34.5 in/38.6 in (87.6 cm/97.8 cm)
Dry Weight	866 lb (393.2 kg)
Outside Radius Circle	32.6 ft (9.9 m) dia
Turning Radius	15.9 ft (4.8 m)
Intersecting Aisle Radius	9 ft (274.3 cm)
Speed Range	15-17 mph (24-27 kph)
Vehicle Warranty	3 yr/3000 hr limited powertrain/frame; 2 yr limited remaining vehicle