



PROPOSAL




XRT1550SE 4x4 Diesel

FEATURES & BENEFITS

- Rustproof aircraft-grade aluminum frame, impact-resistant front body with molded-in color, steel-sided cargo box and tube bumper for long life and good resale value
- Kubota 20 hp (15 kW), 719 cc, liquid-cooled diesel engine
- Exclusive IntelliTrak™ drive system, our automatic, full-time 4-wheel drive system
- 4-link semi-independent rear suspension system for a smoother ride and better ground clearance, even when fully loaded
- 800 -1050 lb (363 - 476 kg) bed capacity with slam-latch tailgate
- Safety features like 4-wheel hydraulic disc brakes, four-point certified roll over protection system (ROPS), retractable seat belts and halogen headlamp
- 2 roomy bench seats, tilt steering wheel, 2 radio/beverage holders and glove box with door
- 2 in (5 cm) receiver hitch for hauling
- Standard colors red or green
- Optional colors Realtree® Hardwoods or Deluxe Hardwoods camouflage
- A wide range of accessories
- A two-year consumer warranty, the best in the industry

SE 4x4 DIESEL SPECIFICATIONS

	Standard features include a Kubota 20 hp (15 kW), 719 cc, liquid-cooled diesel engine, shift-on-the-fly 4-wheel drive, 4 forward-facing seats, an 800 lb (363 kg) capacity bed, semi-independent rear suspension, 4-wheel hydraulic disc brakes, 4-point rollover protection system, seat belts and your choice of 25 in (635 mm) mud or all-terrain tires.
Engine	20 hp (15 kW) @ 3600 rpm per SAE J1995
4WD Engagement	Automatic, IntelliTrak
Electrical System	12-volt, 500 cca
Steering	Self-adjusting rack and pinion, Ackerman
Front Suspension	Independent double A-arms with coil-over shocks
Rear Suspension	4-link semi-independent, coil-over shocks
Brakes	4-wheel hydraulic disc
Chassis	Rustproof, non-corrosive box tube aluminum
Tires	Standard MT 25 x 11 – 12 in (635 x 279 – 305 mm) Optional AT 25 x 10.5 – 12 in (635 x 267 – 305 mm)
Instrumentation	Fuel/hour gauge, low oil and coolant high temperature warning lights
Overall L x W x H	154 x 59 x 80 in (391 x 149 x 204 cm)
Wheelbase	114 in (290 cm)
Ground Clearance Under Differential	8 in (21 cm)
Tire Tread	Front and Rear: 49 in (124 cm)
Weight	1734 lb (786 kg)
Forward Speed	25 mph (40 kph)
Load Bed Size	48 x 50 x 11 in (122 x 127 x 28 cm); 15 ft ³
Maximum Payload	800 lb (363 kg)
Vehicle Rated Capacity	1600 lb (725.5 kg)
Standard Seating	Four
Fuel Tank	6.5 gal (25 L)
Warranty	2-year limited