



## PROPOSAL




# XRT1550SE 4x4 Gas

### FEATURES & BENEFITS

- Rustproof aircraft-grade aluminum frame, impact-resistant front body with molded-in color, steel-sided cargo box and tube bumper for long life and good resale value
- Kawasaki 20.1 rated hp (15 kW), 675 cc air-cooled gas engine
- Exclusive IntelliTrak™ drive system, our automatic, full-time 4-wheel drive system
- 4-link semi-independent rear suspension system for a smoother ride and better ground clearance, even when fully loaded
- 800 -1050 lb (363 - 476 kg) bed capacity with slam-latch tailgate
- Safety features like 4-wheel hydraulic disc brakes, four-point certified roll over protection system (ROPS), retractable seat belts and halogen headlamp
- 2 roomy bench seats, tilt steering wheel, 2 radio/beverage holders and glove box with door
- 2 in (5 cm) receiver hitch for hauling
- Standard colors red or green
- Optional colors Realtree® Hardwoods or Deluxe Hardwoods camouflage
- A wide range of accessories
- A two-year consumer warranty, the best in the industry

### SE 4x4 GAS SPECIFICATIONS

FIND YOUR 	Standard features include a Kawasaki 20.1 rated hp (15 kW), 675 cc air-cooled gas engine, shift-on-the-fly 4-wheel drive, 4 forward-facing seats, an 800 lb (363 kg) capacity bed, semi-independent rear suspension, 4-wheel hydraulic disc brakes, 4-point rollover protection system, seat belts and your choice of 25 in (635 mm) mud or all-terrain tires
<b>Engine</b>	20.1 hp (15 kW) @ 3400 rpm per SAE J1349
<b>4WD Engagement</b>	Automatic, IntelliTrak
<b>Electrical System</b>	12-volt, 500 cca
<b>Steering</b>	Self-adjusting rack and pinion, Ackerman
<b>Front Suspension</b>	Independent double A-arms with coil-over shocks
<b>Rear Suspension</b>	4-link semi-independent, coil-over shocks
<b>Brakes</b>	4-wheel hydraulic disc
<b>Chassis</b>	Rustproof, non-corrosive box tube aluminum
<b>Tires</b>	Standard MT 25 x 11 – 12 in (635 x 279 – 305 mm) Optional AT 25 x 10.5 – 12 in (635 x 267 – 305 mm)
<b>Instrumentation</b>	Fuel/hour gauge, low oil warning light
<b>Overall L x W x H</b>	154 x 59 x 80 in (391 x 149 x 204 cm)
<b>Wheelbase</b>	114 in (290 cm)
<b>Ground Clearance Under Differential</b>	8 in (21 cm)
<b>Tire Tread</b>	Front and Rear: 49 in (124 cm)
<b>Weight</b>	1630 lb (739 kg)
<b>Forward Speed</b>	25 mph (40 kph)
<b>Load Bed Size</b>	48 x 50 x 11 in (122 x 127 x 28 cm); 15 ft <sup>3</sup>
<b>Maximum Payload</b>	800 lb (363 kg)
<b>Vehicle Rated Capacity</b>	1600 lb (725.5 kg)
<b>Standard Seating</b>	Four
<b>Fuel Tank</b>	6.5 gal (25 L)
<b>Warranty</b>	2-year limited