



## PROPOSAL




# XRT1550 Intellitach 4x4 Diesel

### FEATURES & BENEFITS

- Rustproof aircraft-grade aluminum frame, impact-resistant front body with molded-in color, steel-sided cargo box and tube bumper for long life and good resale value
- Kubota 20 hp (15 kW), 719 cc, liquid-cooled diesel engine
- Exclusive IntelliTrak™ drive system, our automatic, full-time 4-wheel drive system
- 4-link semi-independent rear suspension system for a smoother ride and better ground clearance, even when fully loaded
- 800 -1050 lb (363 - 476 kg) bed capacity with slam-latch tailgate
- Safety features like 4-wheel hydraulic disc brakes, four-point certified roll over protection system (ROPS), retractable seat belts and halogen headlamp
- Roomy bench seat, tilt steering wheel, 2 radio/beverage holders and glove box with door
- 2 in (5 cm) receiver hitch for hauling
- Standard colors red or green
- Optional colors Realtree® Hardwoods or Deluxe Hardwoods camouflage
- A wide range of accessories
- A two-year consumer warranty, the best in the industry

### INTELLITACH 4x4 DIESEL SPECIFICATIONS

	Standard features include a Kubota 20 hp (15 kW), 719 cc, liquid-cooled diesel engine, shift-on-the-fly 4-wheel drive, an 800 lb (363 kg) capacity bed, semi-independent rear suspension, 4-wheel hydraulic disc brakes, 4-point rollover protection system, retractable seat belts, your choice of 25 in (635 mm) mud or all-terrain tires, plus the industry's only fully hydraulic quick-changing tool attachment — one vehicle that does it all
<b>Engine</b>	20 hp (15 kW) @ 3600 rpm per SAE J1995
<b>4WD Engagement</b>	Automatic, IntelliTrak
<b>Electrical System</b>	12-volt, 500 cca
<b>Steering</b>	Self-adjusting rack and pinion, Ackerman
<b>Front Suspension</b>	Independent double A-arms with coil-over shocks
<b>Rear Suspension</b>	4-link semi-independent, coil-over shocks
<b>Brakes</b>	4-wheel hydraulic disc
<b>Chassis</b>	Rustproof, non-corrosive box tube aluminum
<b>Tires</b>	Standard MT 25 x 11 – 12 in (635 x 279 – 305 mm) Optional AT 25 x 10.5 – 12 in (635 x 267 – 305 mm)
<b>Instrumentation</b>	Fuel/hour gauge, low oil and coolant high temperature warning lights
<b>Overall L x W x H</b>	With attachment arm: 136 x 58 x 79 in (345 x 147 x 200 cm)
<b>Wheelbase</b>	82 in (208 cm)
<b>Ground Clearance Under Differential</b>	7 in (19 cm)
<b>Tire Tread</b>	Front: 48 in (123 cm) / Rear: 49 in (124 cm)
<b>Weight</b>	1800 lb (815 kg)
<b>Forward Speed</b>	25 mph (40 kph)
<b>Load Bed Size</b>	48 x 50 x 11 in (122 x 127 x 28 cm); 15 ft <sup>3</sup>
<b>Maximum Payload</b>	800 lb (363 kg)
<b>Vehicle Rated Capacity</b>	1200 lb (544 kg)
<b>Standard Seating</b>	Two
<b>Fuel Tank</b>	6.5 gal (25 L)
<b>Warranty</b>	2-year limited