



PROPOSAL



XRT800 Electric

FEATURES & BENEFITS

- Rustproof twin I-beam welded aluminum chassis for long life and good resale value
- Powerful 48-volt electric system with six 8-volt PowerDrive Batteries and optional Single Point Watering System (SPWS)
- 20 in (508 mm) all-terrain tires
- A front body made of impact-resistant plastic to maintain the vehicle's good looks
- A 300 lb (136 kg) with 7 ft³ (20 cm³) capacity dent- and chemical-resistant high-density molded plastic tilting bed box with stake-side pockets for added security
- Dash pocket, cup holders and sport steering wheel for added comfort
- Easy to use lift-style tailgate with tools-free removal
- Standard colors red or green
- Loads of accessories and options, including a fold-down, two-passenger, rear-facing seat, windshield and canopy top
- A two-year consumer warranty, the best in the industry

4x2 ELECTRIC SPECIFICATIONS

	Standard features include a 48-volt electric system with six 8-volt PowerDrive™ batteries, a 300 lb (136 kg) tilting bed box, 20 in (508 mm) all-terrain tires for improved ground clearance, and a roomy bench seat for two
Drive Motor	3.3 hp (2.4 kW) rated, 13 hp (9.6 kW) peak
Engine	NA
Electrical System	48-volt DC, reduced-speed reverse
Steering	Self-adjusting rack and pinion
Suspension	Front and rear tapered mono-leaf springs with dual hydraulic shocks
Brakes	Dual rear wheel self-adjusting with cast-iron drums, single brake pedal and automatic-release park brake
Frame Chassis	Twin I-beam welded aluminum
Tires	20 x 10 - 8 in (508 x 254 - 203 mm) tubeless, four-ply rated
Instrumentation	Low battery warning light
Seating Capacity	Two / Optional four
Overall L x W x H	100 x 45 x 47 in (255 x 114 x 119 cm)
Wheelbase	67 in (169 cm)
Ground Clearance	6 in (14 cm)
Front Tread	35 in (88 cm)
Rear Tread	39 in. (98 cm)
Dry Weight (no Batteries or Fuel)	874 lb (396 kg)
Vehicle Rated Capacity	Vehicle 800 lb (363 kg) / Bed 300 lb (136 kg)
Fuel Tank	NA
Forward Speed	15-17 mph (24-27 km/h)
Warranty	2-year limited

Vehicle shown with optional rear 2-inch ball hitch, nerf bars, and front bumper